

## Pipe Insulation (FM Approval Class Number 4924)

Mechanical piping systems such as those used in heating, ventilating, air conditioning, or refrigeration at temperatures not exceeding 220°F (104°C) sometimes need to be insulated for maximum operational efficiency. The insulations listed below have been tested and found to be acceptable in and of themselves, without needing automatic sprinkler protection.

Each insulation should be used with regard for the size and shape limitations, if any, following their respective listings.

### Pipe Insulation

Products identified with the **GREEN** symbol have attributes that are considered to be "sustainable" by certain outside organizations. FM Approvals verifies the presence of these attributes. Specific attributes for specific products are listed in the individual listings. To facilitate a search for these products in the Approval Guide, first search by the product type you desire and then refine your search to products with the **GREEN** symbol.

### Thermobreak Tube Insulation

Thermobreak Tube Insulation, is a dark grey, flexible closed-cell, physically crosslinked polyolefin foam with factory applied reinforced foil supplied in wall thicknesses up to 25 mm (1 in.), in tubular shape, slit or unslit, for application over pipes up to a 220 mm (8 -5/8 in.) I.P.S. diameter. Aluminum foil tape of minimum width 51 mm (2 in) wide, supplied with a pressure sensitive adhesive is applied to circumferential joints and longitudinal seams.

**GREEN** - This product contains no urea-formaldehyde.

**GREEN** - This product contains no CFC or HCFC.

<b>Company Name:</b>	Sekisui Pilon Pty Ltd
<b>Company Address:</b>	1 - 5 Parraweena Rd, Taren Point NSW 2229
<b>Company Website:</b>	<a href="http://www.sekisuiipilon.com.au">http://www.sekisuiipilon.com.au</a>
<b>Green Product?:</b>	Yes
<b>Listing Country:</b>	Australia
<b>Certification Type:</b>	FM Approved